Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Order this document
by MPS2369/D

Switching Transistors
NPN Silicon

MPS2369
MPS2369A*

*Motorola Preferred Device

Jameco Part Number 26526





CASE 29–04, STYLE 1
TO–92 (TO–226AA)

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V_{CEO}	15	Vdc
Collector–Emitter Voltage	V_{CES}	40	Vdc
Collector–Base Voltage	V_{CBO}	40	Vdc
Emitter–Base Voltage	V_{EBO}	4.5	Vdc
Collector Current — Continuous	I_C	200	mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0	mW mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	–55 to +150	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	°C/W

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector–Emitter Breakdown Voltage(1) (I_C = 10 mAdc, I_B = 0)	MPS2369A	$V_{(BR)CEO}$	15	—	—	Vdc
Collector–Emitter Breakdown Voltage (I_C = 10 μAdc, V_{BE} = 0)	MPS2369,A	$V_{(BR)CES}$	40	—	—	Vdc
Collector–Base Breakdown Voltage (I_C = 10 μAdc, I_E = 0)	MPS2369,A	$V_{(BR)CBO}$	40	—	—	Vdc
Emitter–Base Breakdown Voltage (I_E = 10 μAdc, I_C = 0)	MPS2369,A	$V_{(BR)EBO}$	4.5	—	—	Vdc
Collector Cutoff Current (V_{CB} = 20 Vdc, I_E = 0) (V_{CB} = 20 Vdc, I_E = 0, T_A = 125°C)	MPS2369,A	I_{CBO}	 —	 —	0.4 30	μAdc
Collector Cutoff Current (V_{CE} = 20 Vdc, V_{BE} = 0)	MPS2369,A	I_{CES}	—	—	0.4	μAdc

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

Preferred devices are Motorola recommended choices for future use and best overall value.

© Motorola, Inc. 1996

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)

Characteristic		Symbol	Min	Typ	Max	Unit
ON CHARACTERISTICS						
DC Current Gain(1)		h_{FE}				—
(I_C = 10 mAdc, V_{CE} = 1.0 Vdc)	MPS2369A		—	—	120	
(I_C = 10 mAdc, V_{CE} = 1.0 Vdc, T_A = –55°C)	MPS2369		20	—	—	
(I_C = 10 mAdc, V_{CE} = 1.0 Vdc)	MPS2369		40	—	120	
(I_C = 10 mAdc, V_{CE} = 0.35 Vdc)	MPS2369A		40	—	—	
(I_C = 10 mAdc, V_{CE} = 0.35 Vdc, T_A = –55°C)	MPS2369A		20	—	—	
(I_C = 30 mAdc, V_{CE} = 0.4 Vdc)	MPS2369A		30	—	—	
(I_C = 100 mAdc, V_{CE} = 2.0 Vdc)	MPS2369		20	—	—	
(I_C = 100 mAdc, V_{CE} = 1.0 Vdc)	MPS2369A		20	—	—	
Collector–Emitter Saturation Voltage(1)		$V_{CE(sat)}$				Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MPS2369		—	—	0.25	
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MPS2369A		—	—	0.20	
(I_C = 10 mAdc, I_B = 1.0 mAdc, T_A = +125°C)	MPS2369A		—	—	0.30	
(I_C = 30 mAdc, I_B = 3.0 mAdc)	MPS2369A		—	—	0.25	
(I_C = 100 mAdc, I_B = 10 mAdc)	MPS2369A		—	—	0.50	
Base–Emitter Saturation Voltage(1)		$V_{BE(sat)}$				Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MPS2369		0.7	—	0.85	
(I_C = 10 mAdc, I_B = 1.0 mAdc, T_A = +125°C)	MPS2369A		0.5	—	—	
(I_C = 10 mAdc, I_B = 1.0 mAdc, T_A = –55°C)	MPS2369A		—	—	1.02	
(I_C = 30 mAdc, I_B = 3.0 mAdc)	MPS2369A		—	—	1.15	
(I_C = 100 mAdc, I_B = 10 mAdc)	MPS2369A		—	—	1.60	
SMALL–SIGNAL CHARACTERISTICS						
Output Capacitance (V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)	MPS2369,A	C_{obo}	—	—	4.0	pF
Small–Signal Current Gain (I_C = 10 mAdc, V_{CE} = 10 Vdc, f = 100 MHz)	MPS2369,A	h_{fe}	5.0	—	—	—
SWITCHING CHARACTERISTICS						
Storage Time (I_{B1} = I_{B2} = I_C = 10 mAdc) (Figure 3)	MPS2369,A	t_s	—	5.0	13	ns
Turn–On Time (V_{CC} = 3.0 Vdc, I_C = 10 mAdc, I_{B1} = 3.0 mAdc) (Figure 1)	MPS2369,A	t_{on}	—	8.0	12	ns
Turn–Off Time (V_{CC} = 3.0 Vdc, I_C = 10 mAdc, I_{B1} = 3.0 mAdc, I_{B2} = 1.5 mAdc) (Figure 2)	MPS2369,A	t_{off}	—	10	18	ns

1. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.



Figure 1. t_{on} Circuit



Figure 2. t_{off} Circuit



Figure 3. Storage Test Circuit

* Total shunt capacitance of test jig and connectors.

PACKAGE DIMENSIONS





SECTION X–X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. DIMENSION F APPLIES BETWEEN P AND L. DIMENSION D AND J APPLY BETWEEN L AND K MINIMUM. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.022	0.41	0.55
F	0.016	0.019	0.41	0.48
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	—	12.70	—
L	0.250	—	6.35	—
N	0.080	0.105	2.04	2.66
P	—	0.100	—	2.54
R	0.115	—	2.93	—
V	0.135	—	3.43	—

CASE 029–04
(TO–226AA)
ISSUE AD

STYLE 1:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. “Typical” parameters can and do vary in different applications. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and Ⓜ are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:
USA/EUROPE: Motorola Literature Distribution;
P.O. Box 20912; Phoenix, Arizona 85036. 1–800–441–2447

MFAX: RMFAX0@email.sps.mot.com – TOUCHTONE (602) 244–6609
INTERNET: http://Design–NET.com

JAPAN: Nippon Motorola Ltd.; Tatsumi–SPD–JLDC, Toshikatsu Otsuki,
6F Seibu–Butsuryu–Center, 3–14–2 Tatsumi Koto–Ku, Tokyo 135, Japan. 03–3521–8315

HONG KONG: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852–26629298